

3U FIBER OPTICAL ROTARY PATCH PANEL - SW01-144SCA-xx



Browse on Mobile



Browse on Web

Rotary Swing out 3U patch panels are designed for the FTTH networks, specifically for the street cabinet where full front access is required. This 3U panel accommodates 144 SC/APC adapters and is loaded with bend insensitive pigtails G657A2 and the complete splicing trays and rooting.

FEATURES

- ✓ Holds up to 144 SC Simplex footprint adapters
- ✓ Designed for 19" and ETSI 21" frames
- ✓ Right and left opening
- ✓ Supplied fully loaded ready to splice

APPLICATIONS

- ✓ Datacenter storage area & Central office, POP
- ✓ Fiber to the home (FTTH) Street cabinets
- ✓ LAN/WAN

SPECIFICATIONS

Mounting Type	19" and compatible ETSI 21"
Opening Type	3 Individual Right or Left Hinge swing out trays
Dimension	132 x 482 x 265mm
Material	Anticorrosive Steel and FR polymer
Housing Color	Painted light grey RAL7035
Operating Temperature	−25°C ~ +55°C (5 to 95% RH)
Net Weight	7.5kg

DESIGN - HARDWARE

Slot Type	SC/APC Simplex adapters
Number of Slots	144
Fiber Type	Singlemode Bend Insensitive G657A2 Easystrip
Insertion Loss	IL ≤ 0,20dB / RL 65dB

ORDER INFORMATION

Part Number	Product Description
SW01-144SCA-LF	3U Pivot Panel 144FO SCA loaded Pigtailed SC/APC OS2 G657A2 LSZH Easystrip, Opening Left
SW01-144SCA-RI	3U Pivot Panel 144FO SCA loaded Pigtailed SC/APC OS2 G657A2 LSZH Easystrip, Opening Right