

## 3U FIBER OPTICAL ROTARY SPLITTER PANEL – SW02-128-xx



Browse on Mobile

 [Browse on Web](#)

NEXCONEC® 3U rotary splitter panel is widely used in optical communication networks, completing such functions as splicing, splitting and 128-fiber distribution. It can be installed optical splitter (maximum splitting ratio: two 1X64 optical splitter) to implement optical splitting and capacity expansion. After the product left handed rotated, fixing optical splitter and back panel of splicing tray left handed rotated. Backbone inlet adopt embedded way, convenience for operation and maintenance.

### FEATURES

- ✓ Applied to rackmount 19- or 21-inch installation standard
- ✓ Perfect optical route design to ensure bend radius of fibers greater than 30 mm
- ✓ Pleasing appearance, easy for maintenance and operation
- ✓ Right and left opening
- ✓ Supplied fully loaded ready to splice
- ✓ Compliant with RoHS

### APPLICATIONS

- ✓ Datacenter storage area & Central office, POP
- ✓ Fiber to the home (FTTH) Street cabinets
- ✓ LAN/WAN

## SPECIFICATIONS

<b>Mounting Type</b>	19" or 21"
<b>Opening Type</b>	Right or Left Hinge swing out
<b>Dimension</b>	132 x 482.8 x 215 mm
<b>Material</b>	Anticorrosive Steel and FR polymer
<b>Housing Color</b>	Painted light grey RAL7035
<b>Maximum Capacity</b>	128 SC Adapters
<b>Maximum Splice Tray</b>	2x 12F
<b>Operating Temperature</b>	— 25°C ~ +55°C (5 to 95% RH)
<b>Net Weight</b>	5.5 Kg

## DESIGN - HARDWARE

<b>Slot Type</b>	SC Simplex adapters
<b>Number of Slots</b>	128

## ORDER INFORMATION

Part Number	Product Description
<b>SW02-128-LF</b>	3U Splitter Pivot Panel, 128 SC Adapters Ports Unloaded, Left Opening
<b>SW02-128-RI</b>	3U Splitter Pivot Panel, 128 SC Adapters Ports Unloaded, Right Opening

*\*Custom loading of the panel on demand*

TECHNICAL DRAWING

