

## DOME ENCLOSURE - OC-DO07



Browse on Mobile

 Browse on Web

NEXCONEC® Compact Dome Enclosure is the best designed and innovative solution for fiber cabling installation. It only requires its silicone rubber sealing gasket to ensure the good sealing performance of fiber cable, up to 96FO of fiber count. The different sizes of cable entrances provide the great flexibility for cables installation.

### FEATURES AND APPLICATIONS

- ✓ Up to 96 cores capacity
- ✓ Outdoor Airproofing performance IP68
- ✓ Easy management and maintenance
- ✓ FTTx Access Network
- ✓ Telecommunication network
- ✓ LAN/WAN, CATV

## SPECIFICATIONS

Parameters	Value
Dimensions (HxD)	410 x 205 mm
Weight (Kg)	1.70 - 2.50 Kg
Material	ABS+ PP Fiber Glass
Max. Capacity (Fibers)	96 Fibers
Maximum Number of Splice Trays	4
Capacity of Splice Tray	Max 24 single Fusion splices
Cable Entrances	4
Suitable Fiber Cable OD	Round $\Phi$ 18mm - Oval $\Phi$ 24x35mm
Sealing Structure	Heat Shrink Sealing
Sealing Rating	IP68
Operating Temperature	-40°C ~+65°C
Impact Strength	16 N.m / IK09

## ORDER INFORMATION

Part Number	Product Description
OC-DO07-24	FO Dome Enclosure 24FO H/S
OC-DO07-48	FO Dome Enclosure 48FO H/S
OC-DO07-72	FO Dome Enclosure 72FO H/S
OC-DO07-96	FO Dome Enclosure 96FO H/S