

## DOME ENCLOSURE - OC-DO03



Browse on Mobile

 Browse on Web

NEXCONEC® Compact Dome closure is the best designed and innovative solution for fiber cabling installation. It only requires its silicone rubber sealing gasket to ensure the good sealing performance of fiber cable, up to 96fibers of fiber count. The different sizes of cable entrances provide the great flexibility for cables installation.

### FEATURES AND APPLICATIONS

- ✓ Smaller size
- ✓ Single core splice or mass fusion splice
- ✓ Adequate space for fibers storage
- ✓ Easy operation
- ✓ Lightweight

## SPECIFICATIONS

Parameters	Value
Dimensions (HxD)	410 x 190 mm
Weight (Kg)	2.3-2.5 Kg
Splice Tray	24fibers, max. 6 pieces, splice tray size: 228x120x10mm
Max. Capacity (Fibers)	96 fibers
Number of Inlet/Out Ports	5pcs
Diameter of Fiber Cables	Round port : Ø8-20 Ovale port : Ø8-25
Sealing Structure	Heat Shrink Sealing
Sealing Rating	IP68
Operating Temperature	-40°C ~ +65°C
Impact Strength	16 N.m / IK09

## ORDER INFORMATION

Part Number	Product Description
<b>OC-DO03-24</b>	FO Dome Enclosure 24FO H/S
<b>OC-DO03-48</b>	FO Dome Enclosure 48FO H/S
<b>OC-DO03-72</b>	FO Dome Enclosure 72FO H/S
<b>OC-DO03-96</b>	FO Dome Enclosure 96FO H/S