

FIBER SPLICE PROTECTOR SLEEVES – FSPLxx





Browse on Web

NEXCONEC[®] splice protector sleeve is specifically made to accommodate the bare fibers when fusion splicing. The different lengths of splice protectors offer the flexibility to fiber optic network installers to adapt the variant of splice trays, splice holders and in designing optical modules.

The strength member made with 1.0mm in diameter of stainless steel provides the robust holding to the fibers. The Nexconec splice protector sleeve is the industry standard for durable and lasting protection of single fiber splices in field installations.

FEATURES

- ✓ 3 different length option (40mm, 45mm, 60mm)
- ✓ Easy to use
- ✓ Pack of 100pcs
- ✓ RoHS compliant

APPLICATIONS

- ✓ Fiber splicing in rack mount and wall mount enclosure
- Fiber splicing in rack mount patch panels



SPECIFICATIONS

Parameters	Unit	Value
Sleeve Length	mm	40, 45, 60
Strength Member Diameter	mm	1.0
Outer Tube Material		Polyethylene
Heat Shrink Temp. Range	°C	+90 to +110

ORDER INFORMATION

Part Number	Product Description	
FSPL40	Fiber Splice Protector 40mm (Bag 100pcs)	
FSPL45	Fiber Splice Protector 45mm (Bag 100pcs)	
FSPL60	Fiber Splice Protector 60mm (Bag 100pcs)	