


FTTH DROP CABLE INDOOR/OUTDOOR



Browse on Mobile



Browse on Web

NEXCONEC® FTTH Drop Cable is all dielectric drop cable consisting of 1 to 4, 250µm individually colored optical fibers with Fiber Reinforced Plastic (FRP) strength members and UV resistant Low Smoke Zero Halogen (LSZH) or PE jacket.

FEATURES

- ✓ Single mode options available
- ✓ Compact cable construction
- ✓ FRP strength member
- ✓ Individually colored optical fibers
- ✓ Conforms to IEC standard

APPLICATIONS

- ✓ Ideal use for FTTH applications
- ✓ Horizontal cabling

SPECIFICATIONS

Parameter	Unit	Value
Outer Diameter	mm	2.0 x 3.0
Tensile Strength (Long Term)	N	40
Tensile Strength (Short Term)	N	80
Crush Resistance (Long Term)	N/100mm	300
Crush Resistance (Short Term)	N/100mm	1000
Storage Temperature	°C	-20 ~ +70
Operating Temperature	°C	-20 ~ +70
Cable Weight	Kg/Km	9

ORDER INFORMATION

CF	1	2	3	4	5
----	---	---	---	---	---

CF	1	CABLE CONSTRUCTION	2	FIBER COUNT	3	FIBER	4	JACKET COLOR	5	JACKET MATERIAL
	F	FTTH CABLE	1-4		2D	G652D	W	WHITE	L	LSZH
					A1	G657A1	B	BLACK	E	PE*
					A2	G657A2				

*PE jacket is for outdoor application and is not flame retardant