

## HD MTP®/MPO SPLICE CASSETTE - MP4SPMxxx



Browse on Mobile

 Browse on Web

NEXCONEC® HD MTP®/MPO-Splicing cassettes allow users to fusion splice micro cables, loose-tube cables or ribbon cables to factory assembled pigtails. This metallic body module is designed to splice up to 24F with 2xMPO Base-12 Single mode/Multimode MTP®/MPO connectors. The splice clip is interchangeable allowing different splice protectors to be integrated such as heat-shrink, ribbon, or sandwich (ANT) type.

The HD MTP®/MPO-Splicing cassette is easy to plug into all Nexconec® HD range panels. These MPO splice cassettes are preloaded with adaptors and pigtails, supplied with splicing accessories.

### FEATURES

- ✓ Conform to IEC, EIA-TIA, and Telcordia performance requirements
- ✓ Shuttered dust proof MPO adapters
- ✓ Available in Single mode and Multimode options
- ✓ Single and Ribbon Fiber splice
- ✓ RoHS, REACH & SvHC compliant, Materials Conflict compliant

### APPLICATIONS



- ✓ Telecommunication networks
- ✓ Data centers, Co-location DC
- ✓ LAN or Campus wide Network
- ✓ Broadband network
- ✓ Supports SFP, QSFP, CFP applications

## SPECIFICATIONS

<b>Footprint</b>	HD MP4
<b>Dimensions (WxDxH)</b>	106 x 150 x 35.30 mm
<b>Material</b>	Cold Rolled Steel
<b>Housing Color</b>	Black
<b>Application</b>	HD Panels
<b>Fiber Capacity</b>	24FO, 2xMPO Base-12 MTP®/MPO connectors
<b>Rear Cable Entries</b>	1x Cable gland M12
<b>Adapters Ports</b>	2x MTP®/MPO Base-12 (Male)
<b>Splice Holder</b>	40MM Heat Shrink Sleeves, or Ribbon
<b>Max. Cable Diameter to Use</b>	8 mm
<b>Weight</b>	0.25 Kg

Parameters	Units	SM MTP®/MPO	MM MTP®/MPO
<b>Avg/Max IL– Premium Elite</b>	dB	≤ 0.10/0.35	≤ 0.10/0.35
<b>Return Loss (PC/APC)</b>	dB	≥ 60	≥ 60







## ORDER INFORMATION

Product	Part Number	Product Description
	<b>MP4SPM401</b>	HD Splice Module for 24FO 2xMPO (Male) Elite Base-12 SM SMF OS2
	<b>MP4SPM402</b>	HD Splice Module for 24FO 2xMPO (Male) Elite Base-12 OM4

Notes: Ribbon splice and sandwich (ANT) type are available on request.

\*Add '-FT' for France Telecom color coding. (Example: MP4SPM401-FT)

## RELATED PRODUCTS AND ACCESSORIES

Product	Part Number	Product Description
	<b>MP4PP01</b>	1U 4 Slots HD Modular Fixed Frame
	<b>MP4PP02</b>	1U 4 Slots HD Modular Sliding Patch Panel Unloaded (No front Management)
	<b>MP4PP03</b>	1U 4 Slots HD Modular Sliding Patch Panel Unloaded (Including Front Management)
	<b>MP4PP04</b>	1U 4 Slots HD Modular Fixed Frame (Including Front Management)
	<b>HD3</b>	3U 12 Slots HD Modular Fixed Frame (Including Front Management)
	<b>MP4BK01</b>	Zero RU HD Bracket, 1 Slot (Unloaded)

TECHNICAL DRAWING

