

LOCKABLE INDOOR/OUTDOOR WALL BOX 12 PORTS SC - WP12U1



Browse on Mobile

 [Browse on Web](#)

NEXCONEC® Lockable IP65 & UV Resistant distribution box is supplied unloaded as standard and offers the ability to terminate 12 fibers housed in a strong robust ABS enclosure for indoor and outdoor applications.

An internal detachable tray provides a neat and tidy solution for housing 12 SC simplex connections and splices. The box has 12 patch cord exit points and up to 2 cable entry points which maintain the IP65 rating.

FEATURES

- ✓ UV Resistant & IP65 Rating for external use
- ✓ 12 SC Simplex Adapter type
- ✓ Accepts loose tube, distribution and pre-terminated cables
- ✓ Lockable Door
- ✓ Sealing glands for up to 12 exiting cables + 2 x 8.5mm ~ 13mm incoming
- ✓ Cable
- ✓ Removable splice tray for easy installation

APPLICATIONS

- ✓ FTTH / FTTx Networks
- ✓ Data communication Networks
- ✓ Indoor/Outdoor Application

SPECIFICATIONS

Parameters	Value
Width	205 mm
Height	235 mm
Depth	60 mm
Number of Ports	12 SC Simplex
Number of Cables Entry	Left: 2x Ports (for 8.5 to 13mm OD) Middle: 1x Optional Uncut Round Ports, with 20mm diameter, to load PG16 Gland for cables OD 3mm to 17mm
Number of Cables Exit	Right: 12x Ports (for 2x3mm FTTH Flat Drop Cables)
Max. Splicing Capacity	12 Splices
Material	ABS
Color	Grey RAL7035
Net Weight (Kg)	0.9 Kg
Operating Temperature	-40 °C ~ +60°C
Compliant to	RoHS, REACH, SVHC

ORDER INFORMATION

Part Number	Product Description
WP12U1	In/Out Lockable Wall Box IP65 UV Resistant 12 Positions SC Simplex Unloaded