

LOCKABLE INDOOR/OUTDOOR WALL BOX 48 PORTS SC - WP48U1



Browse on Mobile



Browse on Web

NEXCONEC® Lockable IP65 & UV Resistant distribution box is supplied unloaded as standard and offers the ability to terminate 48 fibers housed in a strong robust ABS enclosure for indoor and outdoor applications.

An internal detachable adaptor tray provides a neat and tidy solution for housing 48 SC simplex connections and splices. Integrated cable tie points are included to secure incoming cables. A locking feature for the door adds extra security when positioned in un-secure areas.

FEATURES

- ✓ SC Simplex / LC Duplex Adapter type
- ✓ Lockable Door
- ✓ IP65 rating & UV Resistant for external use
- ✓ Removable splice tray for easy installation
- ✓ Accepts loose tube, distribution and pre-terminated cables

APPLICATIONS

- ✓ FTTH / FTTx Networks
- ✓ Data communication Networks
- ✓ Indoor/Outdoor Application

SPECIFICATIONS

Parameters	Value
Width	320 mm
Height	420 mm
Depth	125 mm
Number of Ports	48 SC Simplex / LC Duplex
Number of Cables Entry/Exit	<p>2x Big size Uncut Round Ports of 28mm diameter</p> <p>2x Middle size Uncut Round Ports of 23mm diameter, to load M22 Gland for cables OD 8mm to 14mm</p> <p>2x Small size Uncut Round Ports of 15mm diameter, to load M12 Gland for cables OD 3mm to 7mm</p>
Max. Splicing Capacity	96 Splices
Material	PC + ABS
Color	Grey RAL7035
Operating Temperature	-40 °C ~ +60°C
Compliant to	RoHS, REACH, SVHC

ORDER INFORMATION

Part Number	Product Description
WP48U1	In/Out Lockable Wall Box IP65 UV Resistant 48 Positions SC SX / LC DX Unloaded