


LOCKABLE INDOOR/OUTDOOR WALL BOX 6 PORTS SC – WP06U1



Browse on Mobile

 Browse on Web

NEXCONEC® WP06U1 Lockable IP65 distribution box offers the ability to terminate up to 24 fibers housed in a strong robust ABS enclosure for indoor and outdoor applications.

With the ability to use both SC Duplex and LC Quad adapter types offering a flexible solution to the end user, enabling them to incorporate a multi-functional enclosure which allows easy access during installation or re-work with no disturbance of the existing cable or fibers.

Each enclosure has integrated strength member tie positions and bend radius protection with the addition of a removable front door allowing for quick and easy installation.

FEATURES

- ✓ Up to 24FO
- ✓ Multiple adapter options
- ✓ 6 adapter positions
- ✓ Removable splice tray for easy installation
- ✓ Sealing gland for up to 24 existing cables and 1 incoming cable
- ✓ RoHS, REACH & SvHC compliant material

APPLICATIONS

- ✓ Premise installations, telecom networks
- ✓ Data communication networks
- ✓ Indoor/outdoor networks applications

SPECIFICATIONS

Parameters	Value
Dimensions (H x W x D mm)	258 x 186 x 61mm
Max. Fiber Count	24FO
Suitable Adapter Types	SC Duplex, LC Quad
Number of Adapter Positions	6
Cable Entry Port (20mm)	1
Cable Exit Port (20mm)	2
IP Rating	IP65
Material	ABS
Color	Grey (RAL 7035)
Operating Temperature	-40 ~ +60 °C
Weight	0.98 Kg

ORDER INFORMATION

Part Number	Product Description
WP06U1	Wall Termination Box Indoor/Outdoor 6 Ports SC Duplex Lockable, UV Resistant, IP65, Unloaded