


LOCKABLE INDOOR/OUTDOOR WALL BOX 8 PORTS SC – WP09U1



Browse on Mobile



Browse on Web

NEXCONEC® WP09U1 lockable distribution box offers the ability to terminate 8 fibers housed in a strong robust PC+ABS enclosure for indoor and outdoor applications.

With the ability to use both SC Simplex and LC Duplex adapter types offering a flexible solution to the end user, enabling them to incorporate a multi-functional enclosure which allows easy access during installation or re-work with no disturbance of the existing cable or fibers.

The equipment is used as a termination point for the feeder cable to connect with drop cable in FTTx communication network system. The fiber splicing, splitting, distribution can be done in this box, and meanwhile it provides solid protection and management for the FTTx network building.

FEATURES

- ✓ Up to 8FO
- ✓ 8 adapter positions SC simplex or LC duplex
- ✓ Removable splice tray for easy installation
- ✓ Sealing glands for up to 8 exiting cables + 1 incoming cable
- ✓ Accepts loose tube, distribution and pre terminated cables
- ✓ RoHS material compliant

APPLICATIONS

- ✓ Premise installations, telecom networks
- ✓ Data communication networks
- ✓ Indoor/outdoor networks applications

SPECIFICATIONS

Parameters	Value
Dimensions (H x W x D mm)	213 x 163 x 47mm
Max. Fiber Count	8FO
Suitable Adapter Types	SC Simplex, LC Duplex
Number of Adapter Positions	8
Cable Entry Port (20mm)	1
Cable Exit Port (20mm)	2
IP Rating	IP65
Material	PC+ABS
Color	White
Operating Temperature	-40 ~ +85 °C
Weight	0.5 Kg

ORDER INFORMATION

Part Number	Product Description
WP09U1	Wall Termination Box Indoor/Outdoor 8 Ports SC Simplex Lockable, UV Resistant, IP65, Unloaded